



CD4000

Access Control

Codoor codelock – EN Standard

-
- Stand alone programmable codelock for single door
 - Simple and quick to install
 - Internal power supply
 - Built in safety backup

CD4000 is a battery-powered codelock that fits directly on the door inside a building. It locks the door from the outside, and when the correct code is entered it allows the door to be opened once.

The programming of codes is carried out directly on the button panel. The lock can be set manually to “unlock”. Repeated keying of the wrong code blocks the unit from further attempts. The batteries used are standard alkaline or lithium cells.

Lithium cell batteries provide a number of advantages:

- The voltage level is constant during the whole life cycle.
- The battery recovers faster when there is more frequent use of the CD4000.
- They are more environmentally friendly since they have a longer lifetime.
- Storing time can be up to ten years.

The CD4000 is suitable for lock cases with a distance of 72 mm between the center of the door handle and the center of the lock cylinder. It's designed for European standard lock case, following DIN 18251 standard.

Technical data

CD4000	
Colour	Stainless steel
IP rating	IP 30
Environment	Indoors, dry
Operating temperature	0 to +50 °C
Operating voltage	9 VDC. Two batteries, 9V type 6LR61 (not included).
Operational time	Up to 150,000 openings (lithium batteries) or 50,000 openings (alkaline batteries), or one year, whichever comes first
Dimensions (W x H x D)	79 x 255 x 54 mm
Code capacity	9

Details for ordering

Type	Part no	Designation	Weight
CD4000	S24246-C8101-A1	Codoor codelock	1.0 kg

Issued by

Bewator AB
SE-171 24 Solna
Sweden

www.sbt.siemens.com

© 2008 Copyright by
Bewator AB, a Siemens company

Data and design subject to change without notice.
Supply subject to availability.