

Intrusion Panels

SI Control Panels

SI100



Type

Order No.

SI120..



Sintony® control panel 6-22 zones

Multimedia control panel to build-up an universal security system. The Sintony® 120 can be expanded from 6 to 22 inputs and is equipped with all the functions required to implement a high quality security system. Especially for residential and small commercial such as shops, bars, offices and more.

1.5 mm steel housing with tamper contact. Main board with power supply and transformer are integrated. In- and output are freely programmable.

Supply voltage (typical)	230 VAC, ± 10%/-15% / 50 Hz
Current consumption	Max. 160 mA
Battery	12 VDC / 7.2 Ah
Auxiliary power (nominal)	12 VDC / 0.8 A
Number of on-board zones	6
Max. number of hardwired zones	22 (4 SAT12 or SMT12)
Max. number of output modules	1 (SMT44)
Max. number of wireless zones	See installation instruction IEGW6-12
Number of on-board open coll.	4 (max. 12 V / max. 150 mA / 30 R)
Number of on-board relays	1 relay, single-pole, 24 V / 2 A (switching power)
Max. number of outputs	23
Max. number of outputs	19
Number of partitions	2 + 1 common
Number of rooms per partition	6
Event memory (engineer)	200
Event memory (user)	20
Number of keypads	Max. 3
Time function	6 time schedule for auto set/unset per partition
Number of verification devices	Max. 6
Video function	Local cyclical video/picture transmission
Telephone communicator	Optional SML51 (PSTN) or SML61 (ISDN) Digital and Speech transmission
Interfaces	1 RS232 for printer/PC
Operating temperature	0 ~ +40 °C
Dimensions (W x H x D)	266 x 334 x 75 mm
Housing protection	IP30
Weight (without battery)	3.200 kg
Data sheet	009175, A6V10061890

SI120..

SI120CH

Sintony® control panel 6-22 zones Swiss German

See SI120.. for technical overview and note the additional / other specifications:

Language	See software kit
IP-Communication	Option SMN42 and SMN43 enable communication over IP and GSM

BPZ:8009800001