

Verint SmartSight S1700e

DVD QUALITY ETHERNET VIDEO SERVER



Supports IEEE 802.3af
Power-over-Ethernet (PoE) Standard

PRODUCT OVERVIEW

The Verint SmartSight® S1700e Ethernet video server is designed for high-resolution video monitoring and surveillance applications. The S1700e delivers 4CIF, 25 frames per second (fps), MPEG-4-based video over 10/100Base-T networks using cat 5, fibre optic, and wireless media. The S1700e is well suited for applications in which the server is installed at the camera location, because it leverages the embedded LAN infrastructure. The S1700e is built on open standards and is firmware upgradeable for long-term investment protection.

The S1700e video server is powered using IEEE 802.3af compliant Power-over-Ethernet. This feature reduces the number of cables that need to be run and sends power to the camera (up to 5W).

Configuration and management are made easy with Verint nDVR® , Loronix Video Manager™, or SConfigurator™ software.

KEY FEATURES

- ✓ Dual-stream, MPEG-4-based video input
- ✓ High resolution, 4CIF video streaming at 25 frames per second (fps)
- ✓ Scalable resolution from 176 x 128 pixels to 704 x 480 NTSC pixels (176 x 144 to 704 x 576 PAL pixels)
- ✓ Power-over-Ethernet (IEEE 802.3af standard) support, simplifying installation by reducing the number of cable runs
- ✓ All firmware upgradeable via the network (including the video codec)
- ✓ User selection of RTP/IP, UDP/IP, TCP/IP, or multicast streaming
- ✓ SSL-based user authentication
- ✓ RS-232 serial port for integration to access control systems
- ✓ RS-422/485 serial port to support motorised domes and cameras
- ✓ 3 discrete alarm inputs and 1 relay output
- ✓ Video loss alarm
- ✓ Optional bidirectional audio interface supporting microphone or line-level input, and headphone or line-level output

DIGITAL.
DISTRIBUTED.
NETWORKED.

Verint SmartSight S1700e

DVD QUALITY ETHERNET VIDEO SERVER

NETWORK

Interface	Ethernet 10/100Base-T
Connector	RJ-45 jack
Protocols	Transport: RTP/IP, UDP/IP, TCP/IP, or multicast IP Others: DNS and DHCP client
Security	SSL-based authentication

VIDEO

Input	1 composite, 1 Vpp into 75 ohms (NTSC/PAL)
Connectors	BNC female
Compression	MPEG-4-based
Resolution	Scalable from 176 x 128 to 704 x 480 NTSC pixels (176 x 144 to 704 x 576 PAL pixels)
Frame rate	1-25 fps programmable (full motion)
Bandwidth	Configurable between 30 kbps and 4 Mbps

SERIAL PORT

Electrical levels	Port 1: RS-232 (max. 230 kbps) Port 2: RS-422/485 2/4 wires (max. 230 kbps)
Connectors	Port 1: DB-9 Port 2: pluggable screw-terminal strip
Operating mode	Transparent serial port supporting any asynchronous serial protocol

ALARM AND AUDIO

Alarm	Input: 3 dry contact inputs Output: 1 relay contact output (48V AC/DC at 100 mA max.)
Bidirectional audio (optional)	Input: -46 to -3 dBV into 1 kOhm Output: -46 to -3 dBV into 16 ohms min.
Audio connectors	0.14 in. (3.5 mm) input and output stereo jacks

POWER

Supply voltage	48V DC PoE (125 mA); PoE 802.3af
----------------	----------------------------------

PHYSICAL

Enclosure	Metal case with flange mount (black colour)
Size	4.5L x 5.6W x 1.25H in. (115L x 142W x 32H mm)
Weight	0.84 lbs (0.38 kg)
Environmental	32°F to 122°F (0°C to 50°C)
Humidity	95% non condensing at 122°F (50°C)

MANAGEMENT

Configuration	Remote: via nDVR, Loronix Video Manager, SConfigurator, or Telnet Local: via the serial port using any ASCII terminal
Firmware upgrade	Flash memory for upgrade of video codec and application firmware over the network

CERTIFICATION AND REGULATION

USA	FCC part 15 (subpart B, class A)
Canada	ICES-003/NMB-003
Europe	CE marked, EN 55022:1998 class A, EN 55024

WARRANTY

	2-year limited warranty, covering parts and labour 3-year limited warranty, covering parts and labour for S1700e-T-XT and S1700e-T-A-XT
--	--

ORDERING

Part number	S1700e-T
Description	High resolution Ethernet video server encoder with Power-over-Ethernet (PoE) support
Part number	S1700e-T-A
Description	High resolution Ethernet video server encoder with audio and Power-over-Ethernet (PoE) support
Part number	S1700e-T-XT
Description	High resolution Ethernet video server encoder with extended temperature range of -22°F to 144°F (-30°C to 60°C) and Power-over-Ethernet (PoE) support
Part number	S1700e-T-A-XT
Description	High resolution Ethernet video server encoder with extended temperature range of -22°F to 144°F (-30°C to 60°C), audio, and Power-over-Ethernet (PoE) support

OPTIONAL ACCESSORY

Part number	SRM10
Description	Standard black anodised 19-inch (48-cm) rackmount panel (for 10 modules)

By providing this document, Verint Systems is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

Actionable Intelligence, BehaviorTrack, cctvware, Dellis, HealthCheck, Lanex, Loronix, Loronix Video Manager, MotionTrack, microDVR, nDVR, netDVR, and SmartSight are trademarks of Verint Systems Inc. All other registered trademarks, trademarks and any associated logos are the properties of their respective owners.

© 2004 Verint Systems Inc. All rights reserved.