

2U 18-Bay Rackmount Video Recording Appliance Integrated with Milestone XProtect® and Storage Accelerator

Storage Dense Milestone Appliance Equipped with Storage Accelerator

Benefit from scalable storage performance and video processing with the VSS-MS-182-M appliance. This 2U, 2-socket platform brings you scalability and performance to adapt to a variety of the most demanding and process intensive Milestone XProtect applications.

Storage Accelerator


The VSS-MS-182-M comes equipped with a state-of-the-art Storage Accelerator, which allows you to fully utilize its 252TB of raw storage capacity without the need for live video drives. With the Storage Accelerator enabled, read/write speeds exceed that of four hundred and fifty 15K SAS drives combined, ensuring disk bandwidth is never an issue. In addition, the Storage Accelerator's capacitor backup to non-volatile cache helps prevent data loss should a device lose power for added reliability.

System Reliability

System reliability and high availability are guaranteed with redundant 1100W power supplies and RAID 5/6 storage options.

Keep Your Hard Drive

With Video Storage Solutions' Keep Your Hard Drive warranty, your sensitive data and hard drive never leave your control. It also helps you comply with current data privacy regulations and internal company policies by ensuring sensitive information on your hard drive is not compromised, mitigating the risk of expensive civil litigation if confidential customer data or intellectual property were to be exposed.





Back - Dual Processor Models



Back - Single Processor Models

KEY FEATURES

- Up to 252TB of Raw Storage
- Intel® Xeon® Silver 4216 Scalable Processors
- Operating System: Window 10 Pro, Windows Server 2016
- · iDRAC features include:
 - Remote Management
 - Disaster Recovery
 - Critical Resource Monitoring







NVME, SATA & SAS



5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty



Redundant Power



RAID Options: 0, 1, 5, 6, 10




Storage Accelerator

FOR MORE INFORMATION

videoappliances.com sales@videoappliances.com +1.888.305.4993 TECH SUPPORT

support@videoappliances.com

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.





2U 18-Bay Rackmount Video Recording Appliance Integrated with Milestone XProtect® and Storage Accelerator

VSS-MS-182-M

VSS-MS-182x-M

PERFORMANCE		
Bandwidth	Up to 800 Mbps	Up to 1400 Mbps
STORAGE ACCELERATOR FEATURES		
IOPS	135,000	135,000
Capacity	1.6TB	1.6ТВ
Response Time	30 μs	30 μs
Endurance	8.76 Total Petabytes Written	8.76 Total Petabytes Written
SYSTEM		
Processor(s)	Intel® Xeon® Silver Scalable Processor (Up to 16 Cores, 32 Threads, 3.20GHz)	Dual Intel® Xeon® Silver Scalable Processors (Up to 16 Cores, 32 Threads, 3.20GHz per processor)
Processor Passmark	Intel® Xeon® Silver 4210: 15,794 Intel® Xeon® Silver 4216: 16,200	Intel® Xeon® Silver 4210: 16,472 Intel® Xeon® Silver 4216: 22,012
Maximum Storage	Up to 252TB	Up to 252TB
Hard Drives Supported	NVMe, SAS & SATA	NVMe, SATA & SAS
Operating System	Windows 10 Pro, Windows Server 2016	Windows 10 Pro, Windows Server 2016
Memory	Standard Configuration: 16GB (2x 8GB) Maximum Configuration: Up to 768GB LRDIMM, 96GB NVDIMM (24x DDR4 DIMM Slots)	Standard Configuration: 32GB (4x 8GB) Maximum Configuration: Up to 1.5TB LRDIMM, 192GB NVDIMM (24x DDR4 DIMM Slots)
RAID	OS RAID 0, 1; Data RAID 0, 1, 5, 6, 10	OS RAID 0, 1; Data RAID 0, 1, 5, 6, 10
RAID Controller	PERC H740P (8GB NV Cache)	PERC H740P (8GB NV Cache)
Networking	(4) IGbE RJ45 Ports	(4) IGbE RJ45 Ports, (2) 10GbE SFP+ ports
Expansion Slots	(1) Full-height PCle x8, (1) Low-profile x8 slots (In default configuration)	(1) Full-height PCle x8 slots (In default configuration)
USB(s)	Rear (2) USB 3.0, Front (2) USB 2.0, Internal (1) USB 3.0	Rear (2) USB 3.0, Front (2) USB 2.0, Internal (1) USB 3.0
Video Outputs	(I) VGA	(I) VGA
Remote Management	iDRAC Express	iDRAC Express
Manufacturer	Video Storage Solutions	Video Storage Solutions
System Warranty 5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty		
MECHANICAL		
Form Factor	2U Rackmount	2U Rackmount
Rack Support	Sliding Rack Rail with Cable Management Arm	Sliding Rack Rail with Cable Management Arm
Hard Drive Bays	(18) 3.5" Hot Swappable Bays & (2) M.2 SSD Slots	(18) 3.5" Hot Swappable Bays & (2) M.2 SSD Slots
Power Supply(s)	(2) 1100W (100-240VAC) 80 Plus Platinum	(2) 1100W (100-240VAC) 80 Plus Platinum
Maximum Power Draw	775W	860W
Operating Temperature	(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]	(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]
Operating Humidity	5 ~ 90% (non-condensing)	5 ~ 90% (non-condensing)
Dimensions (WxDxH)	19" (482.6mm) x 29.7" (755mm) x 3.4" (86.8mm)	19" (482.6mm) x 29.7" (755mm) x 3.4" (86.8mm)
Max. Weight	73 lbs. (33.lkg)	73 lbs. (33.lkg)

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.