

Not all applications are created equal. With the plug and play format in mind, the RCVO-2415sc is an all-weather 2.4 GHz video receiver with a convenient external antenna input connection. This can provide the flexibility you need to utilize the type of optional high gain antenna that suits your application and range requirements.



ADVANTAGES

- Easy to install – Point and Shoot
- Four user selectable channels available
- Unique external antenna input connection
- Eliminates the need for cabling or trenching
- Receives video from locations normally not possible, convenient or economical with cable
- One Year Limited Warranty

SPECIFICATIONS	RCVO-2415sc
Four User Selectable Channels	2.4108 – 2.4728 GHz
Range (line-of-sight)	Depends on Optional Transmitter and Antenna
Receiver Antenna Type	Requires Optional Antenna and Not Included
Video Format	NTSC or PAL
Video Connector	BNC male @ 75 OHMS –1 Volt P-P
Audio Connector	BNC male @ 600 OHMS –1 Volt P-P
Temperature Range	-30°F – 170°F
Power Supply Included	12 – 14 VDC – Polarity Protected
Current Consumption:	350 mA @12VDC
Dimensions	8.25" x 8.25" x 4.25"
Includes Mounting Bracket	Max 2" Diameter Mast Mount
Weight	2.1kg or 14.8 lbs (each)
FCC / IC Approved	YES

KIT INCLUDES

- All Weather Receiver
- 12VDC Power Supply
- Mounting Bracket and hardware
- Detailed operating and installation instructions



Requires Optional Antenna and Not Included.