Ideal for short to long range receiving when running cable is not possible, economical or convenient. The RX-2445 is mounted in a metal case for improved EMI / RFI shielding and includes a rubber duck antenna to ensure a robust RF signal. With four user selectable frequencies, this system is perfect for applications ranging from surveillance to remote monitoring.

ADVANTAGES

- Eliminates the need for cabling or trenching
- Sends video from locations normally not possible, convenient or economical with cable
- Ideal for portable, temporary and covert surveillance or monitoring applications
- Four user selectable channels
- One Year Limited Warranty



SPECIFICATIONS

| OPERATING FREQUENCY | 2.4108GHz – 2.4728GHz; 4 User Selectable Channels |
|-----------------------|---|
| RANGE (LINE-OF-SIGHT) | 1,000 Feet |
| ANTENNA TYPE | Omnidirectional Rubber Duck |
| VIDEO FORMAT | NTSC or PAL |
| VIDEO CONNECTOR | BNC Female @ 75 Ohms 1 Volt P–P |
| AUDIO CONNECTOR | RCA Female @ 600 Ohms 1 Volt P–P |
| TEMPERATURE RANGE | -22°F to +150°F |
| POWER SUPPLY INCLUDED | 12 VDC Polarity Protected |
| CURRENT CONSUMPTION | 350 mA @ 12 VDC |
| DIMENSIONS | 2.30" x 5.25" x 1.25" |
| WEIGHT | 213g or 7.5 oz |
| FCC / IC APPROVED | YES |

KITS INCLUDE

- VIDEO RECEIVER
- •RUBBER DUCK ANTENNA
- 12VDC POWER SUPPLY
- ONE YEAR LIMITED WARRANTY





