

*Slightly larger than a book of matches, T-2400 Omni-Directional transmitter series, radiates real time, high resolution, color & B&W, video and optional audio signals in a 360 degree pattern. With its omni-directional antenna, minor changes to the transmitter or receiver location are not critical to the overall performance. Ideal choice for building into custom mini camera housings, these mini transmitters are perfectly suited for applications where only a battery is possible.*



## Advantages

- Outperforms 900 MHz for use with color or high resolution cameras
- Outperforms 900 MHz for outdoor / long range transmission
- Requires 2.4 GHz video receiver – not included
- One Year Limited Warranty

SPECIFICATIONS		OMNI SERIES
<b>Channel #1</b>	2.4338 GHz	T-2401od
<b>Channel #2</b>	2.4528 GHz	T-2402od
<b>Channel #3</b>	2.4728 GHz	T-2403od
<b>Channel #4</b>	2.4108 GHz	T-2404od
<b>Antenna Type</b>	Fixed	Omni
<b>Transmitter Frequency</b>		Fixed – Not Selectable
<b>Radiated Power</b>	Low Power	50 mV/m @ 3m
	Optional High Power	80 mW @ 12VDC
<b>Range (Line-of-sight)</b>	Low Power	900 Feet
	Optional High Power	1700 Feet
<b>Video Format</b>		NTSC or PAL
<b>Video Input Connector</b>		RCA male @ 75 $\Omega$ – 1 Volt p-p
<b>Optional Audio Input Connector</b>		RCA male @ 600 $\Omega$ – 1 Volt p-p
<b>Temperature Range</b>		-30°F to 170°F
<b>Power Supply Not Included</b>		8 – 12 Volts DC – Polarity Protected
<b>Current Consumption</b>	Low Power	26 mA @ 5 to 14VDC
	Optional High Power	95 mA @ 12VDC
<b>Dimensions</b>		1"(W) x 2.5"(L) x 0.25"(D)
<b>FCC / Industry Canada Approved</b>		Low Power YES / High Power N/A

Requires 2.4 GHz receiver, not included