


5.8 GHz

All New!

TCO-5808T3 Series

Designed with the harshest environments in mind, the robust TCO-5808T3 series delivers high resolution, real time video. Its rugged IP-67 all-weather enclosure transmits in applications where trenching cable may not be possible, convenient or economical. Choose an optional receiver antenna to maximize your application results.



8-CHANNEL DESIGN



ADVANTAGES

- Easy to install and operate
- Delivers high resolution, **Real-time** video
- Less susceptible to Wireless data networks and other devices
- Rugged all weather IP-67 protective enclosure
- Perfect for commercial, industrial, scientific, law enforcement and government video security applications

KIT INCLUDES

- All Weather Transmitter
- All Weather Receiver
- Operating Instructions
- 12 VDC Power Supplies
- Mounting Brackets
- One Year Limited Warranty
- **Requires Receiver Antenna and not included**





APPLICATIONS INCLUDE

Public Facilities Including;

- Parking Lots
- Gas Stations
- Freeways
- Schools
- Marinas
- Shopping Malls

Commercial / Industrial Facilities Including;

- Construction Sites
- Power Plants
- Airports
- Water Treatment Plants
- Oil & Gas Pipelines
- Property Management



SPECIFICATIONS

TCO-5808T3

Operating Frequency	5.725 GHz – 5.875 GHz; 8 User Selectable Channels
Radiated Power	50mV/m @ 3m
Range (Line-of-Sight)	Depends on Receiver Antenna
Transmitter Antenna Type	3dB Internal Fixed Directional Patch
Receiver Antenna Type	Requires Receiver Antenna and not included
Receiver Sensitivity	-84 dBm
Video Format	NTSC or PAL
Video Connectors	BNC Female @ 75 Ohms 1 Volt P-P
Audio Connector	One Left and One Right BNC Female @ 600 Ohms 1 Volt P-P
Temperature Range	-40°F – 170°F
Power Supply Included	9 – 14 VDC – Polarity Protected
Current Consumption	Transmitter: 230 mA @ 12 VDC Receiver: 330 mA @ 12 VDC
Dimensions	7.0" x 7.0" x 4.5"
Mounting Brackets	Universal Wall / Pole Mount – Included
Weight	0.9kg or 32oz
FCC / IC Approved	Yes