## TX-1293sp

Ideal for short to medium range transmission when running cable is not possible, economical or convenient. This 1.2GHz transmitter is mounted in a metal case for improved EMI / RFI shielding and includes a rubber duck antenna to ensure a robust RF signal. Excellent choice for applications ranging from surveillance to remote monitoring.

## **ADVANTAGES**

- Low Profile Design
- Four user selectable channels
- 3 Watt Super Power Transmitter
- Perfect for law enforcement and government video security applications
- One Year Limited Warranty



## **SPECIFICATIONS**

OPERATING FREQUENCY	1.080GHz - 1.2GHz; 4 User Selectable Channels
RADIATED POWER	3 Watt
RANGE (LINE-OF-SIGHT)	Depends on Optional Receiver
ANTENNA TYPE	Omnidirectional Rubber Duck
VIDEO FORMAT	NTSC or PAL
VIDEO CONNECTOR	RCA Female @ 75 Ohms 1 Volt P–P
AUDIO CONNECTOR	RCA Female @ 600 Ohms 1 Volt P–P
TEMPERATURE RANGE	-22°F to +150°F
POWER SUPPLY INCLUDED	12 – 14 VDC Polarity Protected
CURRENT CONSUMPTION	1400mA @ 12 DVC
DIMENSIONS	1.8" x 2.4" x 1.4"
WEIGHT	161g or 5.6 oz
FCC / IC APPROVED	N/A – Amateur Radio, Law Enforcement, Government & Export

## KIT INCLUDES

- VIDEO TRANSMITTER
- RUBBER DUCK ANTENNA
- TWO 12VDC POWER SUPPLY
- OPERATING INSTRUCTIONS
- ONE YEAR LIMITED WARRANTY







**US Office**: 1711 Cudaback Avenue, Niagara Falls, NY USA 14303 **Canadian Office**: 407 Speers Road, Suite 204, Oakville, ON Canada L6K 3T5

**Toll Free:** 1.888.379.2666 Tel: 905.339.0366 Fax: 905.339.1776