

2.4GHZ

## TXO-2415TL

Easy to install the TXO-2415TL is a fully weatherproof 2.4GHz wireless video transmitter that's ready to operate right out the box. Simply connect a power supply, video cable, aim and shoot. With a range **up to 1,500 feet**, this system is the best choice for short range wireless applications.



**1,500 Feet Range**

### ADVANTAGES

- Easy to install and operate
- Delivers high resolution Real-Time video
- 4 user selectable channels
- Range up to 1,500 feet line of sight
- Perfect for commercial, industrial, scientific, law enforcement and government video security applications



## APPLICATIONS INCLUDE



FREEWAYS



PARKING LOTS



AIRPORTS



CONSTRUCTION SITES



MARINAS



INDUSTRIAL

## SPECIFICATIONS

OPERATING FREQUENCY	2.41GHz – 2.47GHz; 4 User Selectable Channels
RADIATED POWER	50mV/m @ 3m
RANGE (LINE-OF-SIGHT)	Depends on Optional Receiver Antenna
TRANSMITTER ANTENNA TYPE	3dB Internal Left-Hand Circular Polarized
VIDEO FORMAT	NTSC or PAL
VIDEO CONNECTOR	BNC-Male @ 75 Ohms 1 Volt P-P
AUDIO CONNECTOR	One Left BNC-Male @ 600 Ohms 1 Volt P-P
TEMPERATURE RANGE	-40°F to +180°F
POWER SUPPLY INCLUDED	12 – 14 VDC Polarity Protected
CURRENT CONSUMPTION	140 mA @ 12 VDC
DIMENSIONS	8.25" x 8.25" x 4.25"
MOUNTING BRACKETS	Included – Maximum 2" Diameter Mast Mount
WEIGHT	2.0 kg or 4.4 lbs
FCC / IC APPROVED	Yes

## KIT INCLUDES

- ALL WEATHER TRANSMITTER
- OPERATING INSTRUCTIONS
- 12VDC POWER SUPPLY
- MOUNTING BRACKETS AND HARDWARE
- ONE YEAR LIMITED WARRANTY

