DCBDMATRIX CONTROL KEYBOARD

UIDEDTEC

REVISION 094

Microprocessor controlled	
RS485 communication	
Ergonomic design	

DESCRIPTION

The DCBD keyboard is a solution for remote control of the SM series matrix.


This microprocessor controlled keyboard allows you to control the video switching of SM42B-SM82B, SM84B-SM164B.


The operator can manage the following control functions: video switching, sequences and alarm reset, matrix setup through On Screen Display.

The serial communication to the matrix is RS485.

The DCBD can be fed by the supplied external power supply or directly by the matrix, up to a maximum of 700m (2297ft).







<u>mm</u>

1:4

 DCBD

TECHNICAL DATA

GENERAL

Control of max 16 cameras

Alarm reset

Supplied with instruction manual, wide range power supply, 3 power cables, 2 RJ11 telephone cables, 2 jack shunt boxes RJ11

MECHANICAL

Thermo resistant and shock proof ABS box

14 rubber keys

Dimensions: 80x190x205mm (3.2x7.5x8in)

1 connector RJ11

Power supply jack connector

Configuration Dip-Switch

4 LEDs indicating the active monitor

8 LEDs indicating the active camera

2 LEDs indicating the active camera group (cameras 1 to 8 or cameras 9 to 16)

Power supply LED

ELECTRICAL

Power supply

• IN 100-240Vac - OUT 12Vdc, 47/63Hz, 1A

It can be fed directly by matrix SM42B-SM82B, SM84B-SM164B up to a maximum of 700m (2297ft)

PROTOCOLS

Video Line

- VIDEOTEC (1200, 9600, 19200, 38400 baudrate)
- MACRO (1200, 9600, 19200, 38400 baudrate)

COMMUNICATIONS

RS485 line for communication with matrix to a maximum of 1200m (3937ft)

Selection of communication rates

ENVIRONMENT

Indoor

Operating temperature: 0° C / $+40^{\circ}$ C ($+32^{\circ}$ F / $+104^{\circ}$ F)

CERTIFICATIONS

CE EN61000-6-3, EN60950-1, EN55022 Class B, EN50130-4


FCC Part. 15 Class B

RELATED PRODUCTS

SM42B-SM82B Matrix 4/8 inputs and 2 outputss

SM84B-SM164B Matrix 8/16 inputs and 4 outputs

Retrofit on discontinued products: contact VIDEOTEC for further specifications.



Twisted pair RS485 (max distance 1200m / 3937ft)

→ Video-coax only (max distance 350m / 1148ft)

PACKAGE									
Code	Unit weight		Package weight		Package dimensions (WxHxL)		Master carton		
	kg	lb	kg	lb	cm	in	unit		
DCBD	0.6	1.3	1.8	4.0	31.0x17.4x26.4	12.2x6.1x10.4	5		

240