

DCRE485

DATA MULTIPLEXER

REVISION 0945



MAIN FEATURES

1 input - 8 data outputs

RS485 communication


DESCRIPTION

DCRE485 is a serial data distributor used to increase the lines of DTRX3, DTRXDC, DTMRX2, and MICRODEC receivers. The appliance gives serial data back on 8 outputs at the same time, allowing star configurations.

The receiving mode of the input is RS485; the transmission in RS485, takes place at the same time on all 8 outputs.



DCRE485



DCRE485

mm 1:4

DCRE485

TECHNICAL DATA

GENERAL

1 serial input in RS485 mode
 8 RS485 serial outputs the data sending back from the input
 Ability to cascade connection to other units DCRE485
 Supplied with instruction manual, 8 RJ11 telephone cables 6/6 straight through-length about 150cm (59in), 8 RJ11 connections boxes

MECHANICAL

Steel enclosure
 Epoxypolyester powder painting, grey colour
 Dimensions: 222x185x40mm (7.7x7.3x1.6in)

ELECTRICAL

Power supply: 230Vac, 50/60Hz
 Power consumption: 10W
 Protection fuse: 63 mA T 230V

COMMUNICATIONS

Telemetry transmission on serial output RS485 for a max distance of 1200m (3397ft)

ENVIRONMENT

Indoor
 Operating temperature: 0°C / +45°C (+32°F / +113°F)

CERTIFICATIONS

CE EN61000-6-3, EN60065, EN50130-4


RELATED PRODUCTS

Serial input

DCTEL	Keyboard to control matrix and telemetry
DCIR	Infrared Remote Control
DCJ	Keyboard to control matrix, multiplexers and telemetry equipped with three axis joystick
DCT	Touch screen keyboard to control matrix, multiplexers, DVRs and telemetry equipped with three axis joystick

Control on serial output RS485

MICRODEC485	Mini telemetry receiver 8 functions, 24Vac
DTMRX224	Telemetry receiver 12 functions, 24Vac
DTMRX2	Telemetry receiver 12 functions, 230Vac
DTRX324	Telemetry receiver 17 functions, 24Vac
DTRX3	Telemetry receiver 17 functions, 230Vac
DTRXDC	Telemetry receiver 13 functions, for PTH355P
ULISSE	Positioning Unit



---> Twisted pair RS485 (max distance 1200m / 3937ft) telemetry only

PACKAGE

Code	Unit weight		Package weight		Package dimensions (WxHxL)		Master carton unit
	kg	lb	kg	lb	cm	in	
DCRE485	2.4	5.3	2.8	6.2	7.0x27.5x33.0	2.7x10.8x13.0	-