

# USB485

## USB TO RS485 CONVERTER

### MAIN FEATURES

Suitable for connecting a DCJ Keyboard to a PC  
 USB 1.1 - 2.0 Full Speed compliant  
 No external power supply  
 ESD, EFT, Lighting protection at USB and RS485 Data line  
 Transmission speed up to 115.2 Kbps  
 Driver supports: Windows Server 2008 / Windows Server 2008 x64 / Windows Vista / Windows Vista x64 / Windows Server 2003 / Windows Server 2003 x64 / Windows XP / Windows XP x64 / Windows 2000 / Windows 7 / Windows 7 x64 / Windows 8 / Windows 8 x64 / Linux

### DESCRIPTION

The USB485 converter is suitable for connecting a DCJ Keyboard to a PC. This device can be temporary used to update the firmware of a PTZ units (see related products) from console in remote mode: this operation must be performed by service persons. It is also possible to control any RS485 device with a terminal emulator running from the PC.

### TECHNICAL DATA

#### MECHANICAL

Dimensions: 62x21x25mm (2.4x0.8x1in)  
 Unit weight: 0.02kg

#### ELECTRICAL

Connections: SB Type A; RJ11  
 Power supply: +5 VDC by USB connector  
 Consumption: < 100 mA < 100 mA

#### ENVIRONMENT

Indoor

#### COMMUNICATIONS

RS485: TIA-485; 1 line, internal termination (120 ohm ); according to the RJ11 connector VIDEOTEC  
 USB: Compatibility 1.1 /2.0 Full Speed  
 Max. length of the RS485 line: 1200m

#### PROTOCOLS

Any protocol working below 115200 Baud

#### OPERATING SYSTEM

Driver supports: Windows Server 2008 / Windows Server 2008 x64 / Windows Vista / Windows Vista x64 / Windows Server 2003 / Windows Server 2003 x64 / Windows XP / Windows XP x64 / Windows 2000 / Windows 7 / Windows 7 x64 / Windows 8 / Windows 8 x64 / Linux

#### RELATED PRODUCTS

DCJ Keyboard for video and telemetry control  
 ULISSE COMPACT Positioning unit with day/night camera

#### PACKAGE

Model Number	Weight	Dimensions (WxHxL)	Master carton
USB485	0.05kg (0.011lb)		11x8.5x5.5cm (4x3x2in)



USB485

### TECHNICAL DRAWINGS

Sizes in millimeters.

