

VIDEX interface units

INTERFACE UNITS



VIDEX interface units

SP280N1

The SP280 N1 is a self contained fully approved interface unit allowing Videx door panels to be linked to a standard or cordless telephone handset or an analogue input of a PSTN switch board.

The SP280 N1 can be connected in parallel with an existing telephone or video intercom, the unit will allow for the connection of up to a maximum of two telephones.

Features when using a conventional telephone (with no added telephone charges) include:

- Make and receive outside calls (normal ring).
- Receive calls from the door station (quick double ring).
- Open the speech line to the door station.
- Open the door.
- Place one call on hold, whilst another call is answered.

With standard telephone charges applying, the SP280 N1 will also:

- Divert a call from the door station to another telephone number (max. 24 digits) this can be land line based or a mobile telephone.
- Open the door from the diverted telephone using a four digit code + number 0 or 9.
- Program the SP280 N1 from the telephone keypad.

VTS106 & VTS108

VTS106

The VTS106 PABX switch board accepts one, one button door panel and has six telephone extensions and one external telephone line connection. A call from the door panel will ring all connected telephones or only those programmed to receive the call, on acceptance of the call all other telephones are available for intercommunication or making and receiving an external call. A received call from the door panel or an incoming call can be transferred to another telephone extension.

VTS108

The VTS108 PABX switch board accepts two, one button door panels and has eight telephone extensions and one external telephone line connection. A call from either door panel will ring all telephones or only those programmed to receive calls from the door panels, on acceptance of the call, or calls, all other telephones are available for intercommunication or making and receiving an external call. A received call from a door panel or an incoming call can be transferred to another telephone extension.

Additional features

- Dry contact relay output (programmable from 1 to 45 seconds)
- Triac output
- On hold music
- Auto redial
- Extension 1 fails to telephone line during a mains failure
- Metal stove enamel enclosure

VTS106	VTS108
1	2
0	2
yes	yes
yes	yes
yes	yes
yes	yes



Videx Security Limited: 1 Osprey, Trinity Park, Trinity Way, London E4 8TD

Tel: 020 8523 5800 **Fax:** 020 8523 5825 **www:** videx-security.com **email:** info@videx-security.com

Northern Office: 5-7 Chillingham Industrial Estate, Chapman Street, Newcastle upon Tyne NE6 2XX

Tel: 0191 224 1558 **Fax:** 0191 224 1559