PowerMaxExpress

Ultra-compact Wireless Security – With Internal Communications Options



Visonic's PowerMax®Express packs outstanding func-tionality into an exceptionally small, wireless control panel. It delivers all the reliability and features that homeowners and professional installers need, providing a highly cost-effective solution. Unique among its size class, this sleekly designed control panel offers the flexibility to add internal GSM/GPRS or IP communications modules according to the needs on-site. Easy to install and use, and compliant with international standards, the PowerMaxExpress provides the ideal solution for today's highly competitive market.

- Modern, clean design that fits any décor
- Compact, nearly invisible on wall
- All-in-one, self-contained system
- Versatile internal communications options
- Easy installation and intuitive operation
- Extensive range of accessories and expandability options



PowerMaxExpress

Compact, modern design

- Small size, nearly invisible on the wall
- Very clean, stylish design fits into any modern décor

All-in-one, self-contained panel

- Standard PSTN communicator
- Optional plug-in GSM/GPRS and IP* internal communications modules, field-upgradable
- LCD and a full-function keypad
- Highly cost-effective solution for black-box type installation, with one-way or two-way keypads, keyfobs and wireless sirens

High reliability and performance

- Main PCB board is protected from accidents and sabotage
- Outputs are protected against short circuits
- External transformer and 12-hour backup battery included
- Two-way wireless system with diversity antenna facilitates highly reliable radio communication
- Partitions version available (up to 4)
- Designed to comply with most international standards and regulations, including: FCC, CE and EN50131 grade 2

Easy installation and operation

- Intuitive operation, enrollment and programming
- Compatible with all Visonic peripherals including two-way wireless sirens and keypads

Specifications

Available frequencies: 868, 433, 315

Number of zones: 28 wireless + 1 hardwired input

User codes: 8

Battery type: 12-hour back-up - 4.8V, 1300mAh Power supply (external): Europe: 230VAC 50Hz input, 9VAC

700mA output

USA: 120VAC 60Hz input, 9VAC

1000mA output

Reporting format options: SIA, Contact ID and SIA/IP

Size: 193 x 178 x 50mm (7-5/8 x 7 x 2in)

Weight: 658gr (23oz)

RF system: Two-way + diversity antenna

Wide range of wireless accessories

Extend the value of your offering with these recommended wireless transmitters and detectors.**



CO Detector



Keyfob



Two-way Keyfob



Temperature Detector



Two-way Keypad



GSM/GPRS Modules



Smoke Detector



Remote Commander



Motion Detector



Flood Detector



Gas Detector



Curtain Detector



Outdoor Siren



Indoor Siren



Magnetic Contact

- * All add-on communications modules need to be purchased separately. The IP module is expected to be available during 2009.
- ** Partial list; actual design may be different to the design in the images. Contact Visonic to get a full list of more than 30 types of available accessories.
 - **Visonic** and PowerMax are registered trademarks of Visonic Ltd. Other names are the property of their owners. Visonic reserves the right to change information or specifications without notice.

VISONIC LTD. POWERMAX EXPRESS DATA SHEET ENG C-800513 (Rev.01)

Designed by: Linor Ankri