

# Xtralis Integrated Security and Access Control V3500

High Capacity Digital Video Recorder / Server

## Description

The Xtralis V3500 is an innovative, high capacity digital video recorder/server that provides virtually unlimited, encrypted network video storage using a patented process which dramatically reduces power consumption.

The V3500 provides unlimited storage and unlimited archiving in one unit using patent-pending Xtralis Cold Disk Technology™. Unlike other storage servers that use constantly running disk drives to record video streams and security data, the V3500 CDT server dynamically routes data to multiple on-board storage modules. This distributed approach to data storage allows modules to be powered down when not in use, resulting in a reduction in energy consumption and heat dissipation of more than 50% versus traditional storage options.

The V3500 delivers multi-codec video streams (MPEG-4, H.264, MJPEG) making it suitable for centralised, decentralised, LAN/WAN infrastructures, and local/remote video applications.

## Features

- With long-term storage and retrieval capabilities, easily swappable storage cartridges, and a service-friendly architecture, the V3500 is revolutionary in design and performance.
- The V3500 uses a secure encrypted storage format with fully redundant (auto-balancing) processing and storage.
- The V3500 is fully interoperable with the Xtralis 3000 Series family of products, including the V3100 for video and audio recording and transmission, the V3001 for video wall applications, and the S3000 for IP-based access control.
- The V3500 includes a web-based interface and integrated software for viewing and control.

## Key Benefits

- Significant energy savings with patent-pending Cold Disk Technology
- Powerful, integrated real-time archiving for effective bandwidth optimisation
- Virtually unlimited video storage (>1000 TB)
- Easy swappable storage cartridges
- Highly secure encrypted storage format
- Service friendly architecture with auto balancing processing and storage
- High reliability central and decentralised storage support
- Multi-codec MPEG-4, H.264, MJPEG

## Xtralis Security Solution product family



# Xtralis Integrated Security and Access Control V3500

High Capacity Digital Video Recorder / Server

## Specifications

<b>Processor</b>	Single or Dual CPU; Quad Core Xeon CPU
<b>Storage</b>	SATA DAS over SAS BUS disc storage for 16 cartridges with 250, 400, 750 or 1000 GB HDD / 7200 rpm
<b>RAM</b>	4 GB
<b>Drives</b>	5 1/4 DVD-ROM; Drive protected bootable USB flash key
<b>Ethernet</b>	Dual 10/100/1000 Mbps auto negotiate, IEEE802.1d (STP) Compliant
<b>Operating System</b>	Linux
<b>Video Compression</b>	MPEG-4 , H.264 and MJPEG
<b>Video Resolution</b>	(*) Video stream input adjustable (dependent): cif/2cif/Dcif/4cif/VGA/Mpixel...
<b>Images/second</b>	(*) Video stream input adjustable (dependent): 30 ips NTSC / 25 ips PAL, 4cif/VGA 18 ips Mpixel
<b>Bandwidth</b>	(*) Video stream input adjustable (dependent): compression, ips, resolution
<b>Protocols</b>	TCP/IP, NTP, ARP, ICMP, SNMP, SSH, HTTP, HTTPS, IPV4, IPV6 ready
<b>Performance</b>	Full redundancy and auto-balancing through V3500 units
<b>Recording</b>	Continuous, Job scheduled, Event
<b>Software</b>	Web browser interface and M3000 security management software
<b>Housing</b>	V3500:CPU 19"/ 1U x 740mm (29.1") D Colour: black; Weight: 12.5 kg (27.6 lbs); Indoor use V3500:STU 19"/3U x 700mm (27.6") D Colour: black; Weight: 19.5 kg (43 lbs); Indoor use V3500:HDC bay colour: grey/black – weight: 0.950 kg (2.1 lbs)
<b>Power supply</b>	V3500:CPU: redundant PSU (670 W, 100-240 VAC, 50/60 Hz) V3500:STU: redundant PSU (each 400 W, 100-240 VAC, 50/60 Hz)
<b>Temperature</b>	Operation: 5 - 40°C (40 - 104°F) 0 - 95% RH non-condensing, overheat indicators
<b>Product Codes</b>	<b>V3500:CPU:</b> Server Processing Unit, part number: 09003200 <b>V3500:STU:</b> JBOD DAS with dual PSU and SAS BUS (16 trays) part number: 09003201 <b>V3500:HDC:</b> 250 GB SATA disc / 7200 rpm, part number: 09003210 400 GB SATA disc / 7200 rpm, part number: 09003211 750 GB SATA disc / 7200 rpm, part number: 09003212 1 TB SATA disc / 7200 rpm, part number: 09003213
(*) video stream: The Xtralis V3500 can receive video streams from several sources: IP camera, IP server, V3100, PC producing an image, etc. The 3500 unit supports multiple codec video streams with standard MPEG-4, H.264 and MJPEG compatibility.	

### V3500:CPU - 19" Rack



<b>Housing Dimension</b>	19"/1U x 740 mm (29.1") D
<b>Colour</b>	Black
<b>Weight</b>	12.5 kg (27.6 lbs)

### V3500:STU - 19" Rack



<b>Housing Dimension</b>	19"/3U x 700 mm (27.6") D
<b>Colour</b>	Black
<b>Weight</b>	19.5 kg (43 lbs)

### V3500:HDC - Cartridge



<b>Colour</b>	Grey/Black
<b>Weight</b>	0.950 kg (2.1 lbs)

www.xtralis.com

The Americas +1 781 740 2223 Asia +852 2916 8894 Australia and New Zealand +61 3 9936 7000  
Continental Europe +32 56 24 1951 UK and the Middle East +44 1442 242 330

The contents of this document are provided on an "as is" basis. No representation or warranty (either express or implied) is made as to the completeness, accuracy or reliability of the contents of this document. The manufacturer reserves the right to change designs or specifications without obligation and without further notice. Except as otherwise provided, all warranties, express or implied, including without limitation any implied warranties of merchantability and fitness for a particular purpose are expressly excluded.

This document includes registered and unregistered trademarks. All trademarks displayed are the trademarks of their respective owners. Your use of this document does not constitute or create a licence or any other right to use the name and/or trademark and/or label.

This document is subject to copyright owned by Xtralis AG ("Xtralis"). You agree not to copy, communicate to the public, adapt, distribute, transfer, sell, modify or publish any contents of this document without the express prior written consent of Xtralis.

Doc. no. 14536\_03

 **xtralis**  
SECURITY SOLUTIONS®