

Be part of a greener future

CARBON FOOTPRINT COMPARISON REPORT 2010



alpro®
Architectural Hardware

Who says size doesn't matter?

It's About Reducing Your Carbon Footprint...


Electromagnetic Locking Devices are used on all types of doors and are usually installed in conjunction with access control or intercom systems. This report compares the new and uniquely engineered locking solution VORTEX 2400 with a Conventional 600kg Electromagnetic Locking Device.

Conventional 600kg Electromagnetic Locking Devices are large, extremely heavy and have high power consumption in operation.

The Alpro product VORTEX 2400 is different.

It is 75% smaller and has just 10% of the weight of a traditional Electromagnetic Lock, without compromising any of the security or safety requirements vital for this kind of device. In fact it actually enhances the security requirements with its patented "Early Warning" alarm and long distance backlight features.

This report compares the new VORTEX 2400 and a Conventional 600kg Electromagnetic Locking Device on carbon footprint and total energy consumption on both a raw material and finished product level.



ACTUAL SIZE
Conventional Electromagnetic Lock 600kg Holding Force



ACTUAL SIZE
VORTEX Mechanical Electro Magnetic Lock 680kg Holding Force

NOTE: The physical size, quantity and types of raw materials used to manufacture a Conventional 600kg Electromagnetic Locking Device are comparable or in fact identical, to other similar performance magnetic locks on the market, including KABA, Gianni, Securitron and Schlage.

alpro[®]
Architectural Hardware

VORTEX 2400 Devices

Securing The Pathway To Environmental Change

Alpro & Environmental Sustainability

Alpro shares with the world a growing concern for the future of our global environment. It is important that all industries are aware of the environmental impact of the manufacture and use of their products. This implies a need to reinvent and/or improve existing products and the manufacturing technologies used to produce them.

With this in mind Alpro a leading company in Electric and Electronic Locking Solutions, has taken the initiative and created a new electromechanical locking device, the VORTEX 2400. Primary objectives in the development of this device were to meet the highest safety and security standards, and to produce a more environmentally sustainable product.

Calculations

Based on one single unit of each device.

By breaking down each product into their basic elements (aluminium, iron, copper, epoxy and plastic), and aided by the use of a state-of-the-art, 3-D CAD program a comparison was made of the environmental impact of the VORTEX 2400 and the Conventional 600kg Electromagnetic Locking Device. This developed a picture of how both products affect the environment in terms of their carbon footprint, and the total amount of energy consumed to manufacture the devices.

- The comparison considered the following factors:
- raw material production
 - manufacturing of the device



Live Project Australia

We have then applied the calculations to a live project:

The Actew AGL Building in Canberra, A.C.T. Calculations were made of the carbon footprint, energy consumption and standby battery capacity in the manufacturing process as well as the annual energy savings and standby battery capacity offered by installing VORTEX 2400 devices rather than Conventional 600kg Electromagnetic Locking Device.

Analysis of Carbon Footprint (Manufacturing)



The tables and charts below visually and numerically depict carbon emissions values and the total energy consumed by both products during the manufacturing process. These values represent the carbon emissions released, in kg of CO₂, when producing a single unit as a by-product during the manufacture of both raw materials and finished products.



MATERIAL	CONVENTIONAL 600kg ELECTROMAGNETIC LOCKING DEVICE	VORTEX 2400	SAVINGS	PERCENTAGE REDUCTION
ALUMINIUM	11.02	4.91	11.58 kg of CO ₂	63%
IRON	5.89	1.28		
PLASTIC	0.67	0.32		
EPOXY	0.41	0.07		
COPPER	0.32	0.15		
TOTAL (kg of CO ₂)	18.31 kg of CO ₂	6.73 kg of CO ₂		

Analysis of Energy Consumption (Manufacturing)

These tables and charts depict the total energy consumed in a single unit, measured in kW-h throughout the manufacturing process of a Conventional 600kg Electromagnetic Locking Device and a VORTEX 2400.



MATERIAL	CONVENTIONAL 600kg ELECTROMAGNETIC LOCKING DEVICE	VORTEX 2400	SAVINGS	PERCENTAGE REDUCTION
ALUMINIUM	38.25	14.57		
IRON	20.70	4.49		
COPPER	3.33	0.48		
PLASTIC	2.82	1.29		
EPOXY	1.07	0.19		
TOTAL kW-h	66.17 kW-h	21.02 kW-h	45.15 kW-h	68%

Computations

Carbon Footprint (Manufacturing)

Comparing the manufacturing carbon emissions results indicates that the VORTEX 2400 (with 6.73kg of CO₂) has a far "greener footprint" than the Conventional 600kg Electromagnetic Locking Device (with 18.31kg of CO₂). The 11.58kg difference in the amount of CO₂ produced as a by-product leads to a 63% reduction in carbon emissions. This confirms the VORTEX 2400 as an environmentally superior product.

Energy Consumption (Manufacturing)

With a total energy consumption level of 21 kW-h, the VORTEX 2400 consumes 68% less energy during manufacturing compared to the 66kW-h of the Conventional 600kg Electromagnetic Locking Device. This calculation is derived by comparing all the materials needed to produce the two products.

The VORTEX 2400 Environmental Advantage

The results of the carbon footprint analysis and comparison of the Conventional 600kg Electromagnetic Locking Device and the VORTEX 2400 confirms with certainty that the VORTEX 2400 has a significantly lower impact on the environment.

The CO₂ emissions and the total energy consumed to produce the VORTEX 2400 is significantly lower than the Conventional 600kg Electromagnetic Locking Device due to a number of factors:

- Improvement in design (smaller and more compact)
- Lesser quantities of material used (Conventional 600kg Electromagnetic Locking Device is far greater in physical size and weight)
- More efficient methods of production (modern technologies used to manufacture and assemble the product e.g. CNC machinery)



Live Project, Australian Capital Territory

PROJECT

Actew AGL Fit Out

Bunda St Canberra, ACT 2600

ARCHITECTS

Cox Humphries Moss Architects Kingston

22 Jardine St Kingston, ACT 2604

FIT OUT PROJECT MANAGER

Construction Control

1 Torrens St Braddon, ACT 2612

SECURITY CONSULTANT

John Raineri & Associates

17/169 Newcastle St Fyshwick, ACT 2609

SECURITY

SNP Security

Unit 3/ 45-51 Grimwade St Mitchell, ACT 2911

LOCKSMITHING

Essex Locksmiths

Unit 5/6 9 Brookes St Mitchell, ACT 2911

Implementation of the Live Project

In February 2010, the security consultant agreed to change many of the security locking devices on the project from Conventional 600kg Electromagnetic Locking Device to the VORTEX 2400. A total of 65 devices are installed on the project.


Based on our previous calculations of carbon footprint and energy consumption along with standby battery size and annual electricity consumption in operation, the computations indicate the following.

NOTE: The calculations are based on the devices being powered up 24/7.



Analysis of Carbon Footprint (Manufacturing)


The tables and charts below, visually and numerically depict the amount of carbon emissions generated in manufacturing 65 Conventional 600kg Electromagnetic Locking Devices compared to 65 VORTEX 2400 devices.



CARBON FOOTPRINT (MANUFACTURING 65 LOCKS)	CONVENTIONAL 600kg ELECTROMAGNETIC LOCKING DEVICE	VORTEX 2400	SAVINGS	PERCENTAGE REDUCTION
	1190 kg of CO ₂	437 kg of CO ₂	753 kg of CO ₂	63%

Analysis of Energy Consumption (Manufacturing)


These tables and charts depict a comparison of the total energy consumed during manufacturing process of 65 Conventional 600kg Electromagnetic Locking Device compared to 65 VORTEX 2400 devices, measured in kW-h.



ENERGY CONSUMPTION (MANUFACTURING 65 LOCKS)	CONVENTIONAL 600kg ELECTROMAGNETIC LOCKING DEVICE	VORTEX 2400	SAVINGS	PERCENTAGE REDUCTION
	4301.05 kW-h	1366.3 kW-h	2934.75 kW-h	68%


Analysis of Electricity Consumption in Operation

The chart and table below compares the **annual electricity** usage of 65 Conventional 600kg Electromagnetic Locking Devices compared to that of 65 VORTEX 2400 devices in operation onsite running on 24 Volt DC.



Standby Battery Comparison (24hr Standby)

Based on the savings in electricity (power) consumption provided by the VORTEX 2400 devices, the standby batteries required to provide 24hr locking in the event of a power outage, are reduced considerably in physical size and capacity.



Calculate your Project

Analysis of Carbon Footprint (Manufacture)

	NUMBER	KG OF CO ₂	TOTAL KG OF CO ₂	TOTAL SAVING KG OF CO ₂
NUMBER OF CONVENTIONAL MAGNETIC LOCKS ELECTROMAGNETIC LOCKS		x 18.31 =		
NUMBER OF VORTEX 2400 DEVICES		x 6.73 =		

Analysis of Energy Consumption (Manufacture)

	NUMBER	kW-h	TOTAL kW-h	TOTAL SAVING kW-h
NUMBER OF CONVENTIONAL MAGNETIC LOCKS ELECTROMAGNETIC LOCKS		x 66.17 =		
NUMBER OF VORTEX 2400 DEVICES		x 21.02 =		

Annual Electricity Consumption (365 Days x 24 Hours)

	NUMBER	kW-h	TOTAL kW-h	TOTAL SAVING kW-h
NUMBER OF CONVENTIONAL MAGNETIC LOCKS ELECTROMAGNETIC LOCKS		x 51.52 kW-h		
NUMBER OF VORTEX 2400 DEVICES		x 29.43 kW-h		

Capacity for 24 Hours Standby Batteries

	NUMBER	A-h	TOTAL A-h	TOTAL SAVING A-h
NUMBER OF CONVENTIONAL MAGNETIC LOCKS ELECTROMAGNETIC LOCKS		x 5.88 A-h		
NUMBER OF VORTEX 2400 DEVICES		x 3.35 A-h		



CARBON FOOTPRINT COMPARISON REPORT 2010
WALKING GENTLY ON OUR PLANET

alpro[®]
Architectural Hardware

IEC Limited Harwell Rd Nuffield Estate Poole BH17 0BD Great Britain

Registered in England 1925537



T 01202 676262
F 01202 680101
E info@alpro.co.uk
W www.alpro.co.uk